



Commercial Soap

Universal floor cleaner

Commercial Soap may be used for the cleaning of wood, regardless of wood species and surface treatment, as well as for tiles, vinyl and stone surfaces etc. The soap is especially suitable for high frequently cleaning of wood floors.

- Effective care and cleaning of all floors
- Particularly suitable for large flooring areas exposed to high frequent cleaning
- May be used both manually and with machine
- EN 71-3 Safe for childrens toys

Application area

For cleaning of wood, regardless of wood species and surface treatment, as well as for tiles, vinyl and stone surfaces etc.

Work description

Preparation

Very dirty floors may be cleaned with WOCA Intensive Wood Cleaner first. Commercial Soap can also be used in a floor washing machine.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Manual cleaning: Mix 250 ml Commercial Soap with 10 L of water for the daily cleaning. Wash the floor lengthwise the wood grain. For best results, use two buckets: one with soap water and the second with clean water to rinse the dirty mop. It is important that no water is left on the floor. Use only little water to obtain a satisfactory result. Cleaning with machine: 5-20 ml to 1 L of water, depending on how dirty the surface is.

Drying time

Surface Dry: 30 minutes at 20°C

Technical data

Declaration: 5% or over but less than 15%: Soap.

Density: 1.00-1.10 g/ml.

pH-value: pH 9-10

Shelf life: 2 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 320-400 m²/L

Colours: Natural

Cleaning of tools: Use water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight).
Store frost-free during winter and cool during summer.

Packaging: 5 L

Dilution: Water

Odour: Faint

Solid content: 10-20%

Mixing ratio: 125 ml to 5 L water.

Maintenance and related products

WOCA Denmark A/S
Tværvvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.