

ANTI GRAFFITI C1 500ML QUICK TECH - A25352



S.I.C.O.

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : ANTI GRAFFITI C1 500ML QUICK TECH

Product code : A25352.

UFI : EEGD-K3GF-ANCD-JFVP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent

1.3. Details of the supplier of the safety data sheet

Registered company name : SICO.

Address : 577 RUE DU POMMARIN - BP 16 - .38 341.VOREPPE.France.

Telephone : 04 76 50 85 50. Fax : 04 76 50 85 67.

sico.fds@sico.net

www.sico.net

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

Other emergency numbers

Une liste des numéros d'appels d'urgence pour l'ensemble des pays de l'Union Européenne est disponible sur le site internet de l'Echa (<https://echa.europa.eu/fr/support/helpdesks>)

A list of emergency telephone numbers for all European Union countries is available on the Echa website (<https://echa.europa.eu/fr/support/helpdesks>)

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

May produce an allergic reaction (EUH208).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

The propellant gas is not taken into account when determining the health and environmental classification of the mixture.

2.2. Label elements

Detergent mixture (see section 15).

The mixture is an aerosol fitted with a sealed spray attachment.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

DANGER

Product identifiers :

EC 919-857-5 HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Additional labeling :

EUH208 Contains D-LIMONENE. May produce an allergic reaction.

Hazard statements :

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

|                                                                                                                              |                                                                                                |
|------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| H336                                                                                                                         | May cause drowsiness or dizziness.                                                             |
| EUH066                                                                                                                       | Repeated exposure may cause skin dryness or cracking.                                          |
| Precautionary statements - General :                                                                                         |                                                                                                |
| P101                                                                                                                         | If medical advice is needed, have product container or label at hand.                          |
| P102                                                                                                                         | Keep out of reach of children.                                                                 |
| Precautionary statements - Prevention :                                                                                      |                                                                                                |
| P210                                                                                                                         | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211                                                                                                                         | Do not spray on an open flame or other ignition source.                                        |
| P251                                                                                                                         | Do not pierce or burn, even after use.                                                         |
| P261                                                                                                                         | Avoid breathing spray.                                                                         |
| P271                                                                                                                         | Use only outdoors or in a well-ventilated area.                                                |
| Precautionary statements - Response :                                                                                        |                                                                                                |
| P304 + P340                                                                                                                  | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                     |
| P312                                                                                                                         | Call a POISON CENTER/doctor/.../if you feel unwell.                                            |
| P331                                                                                                                         | Do NOT induce vomiting.                                                                        |
| Precautionary statements - Storage :                                                                                         |                                                                                                |
| P410 + P412                                                                                                                  | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.                   |
| Precautionary statements - Disposal :                                                                                        |                                                                                                |
| P501                                                                                                                         | Dispose of contents/container according to the local rules.                                    |
| Other information :                                                                                                          |                                                                                                |
| Do not spray for a long time.                                                                                                |                                                                                                |
| Use and keep only in well ventilated zones. Do not use for a usage other one than the one for which the product is intended. |                                                                                                |

### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 59 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

| Identification                                                                                                         | Classification (EC) 1272/2008                                                                      | Note              | %                   |
|------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|-------------------|---------------------|
| INDEX: 601-004-00-0<br>CAS: 106-97-8<br>EC: 203-448-7<br><br>BUTANE                                                    | GHS02, GHS04<br>Dgr<br>Flam. Gas 1A, H220                                                          | C<br>[i]<br>[vii] | 25 $\leq$ x % < 50  |
| EC: 919-857-5<br>REACH: 01-2119463258-33<br><br>HYDROCARBONS, C9-C11, N-ALKANES,<br>ISOALKANES, CYCLICS, <2% AROMATICS | GHS07, GHS08, GHS02<br>Dgr<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336<br>EUH066 |                   | 10 $\leq$ x % < 25  |
| CAS: 34590-94-8<br>EC: 252-104-2<br>REACH: 01-2119450011-60<br><br>DIPROPYLENE GLYCOL MONOMETHYL<br>ETHER              |                                                                                                    | [i]               | 2.5 $\leq$ x % < 10 |
| CAS: 1569-01-3<br>EC: 216-372-4<br>REACH: 01-2119474443-37<br><br>1-PROPOXYPROPAN-2-OL                                 | GHS07<br>Wng<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319                                          |                   | 0 $\leq$ x % < 2.5  |

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

|                                                   |                                                                                                                                                                                               |  |               |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------|
| CAS: 5989-27-5<br>EC: 227-813-5<br><br>D-LIMONENE | GHS02, GHS07, GHS08, GHS09<br>Dgr<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>Skin Irrit. 2, H315<br>Skin Sens. 1B, H317<br>Aquatic Chronic 3, H412<br>Aquatic Acute 1, H400<br>M Acute = 1 |  | 0 ≤ x % < 2.5 |
|---------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------|

**Information on ingredients :**

(Full text of H-phrases: see section 16)

Substances may not have a REACH Registration No.. because they are manufactured / imported in quantities less than 1 ton / year, or they are complex substances or they are exempted from registration under REACH.

[i] Substance for which maximum workplace exposure limits are available.

[vii] Propellant gas

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. description of first aid measures**

**In the event of exposure by inhalation :**

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

**In the event of splashes or contact with skin :**

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Specific and immediate treatment :**

No data available.

**Information for the doctor :**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist

---

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

---

- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

See Section 7 for information on safe handling.

---

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

Do not pierce or burn, even after use.

Never inhale this mixture.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- European Union :

| CAS                                                  | VME-mg/m3 : | VME-ppm : | VLE-mg/m3 : | VLE-ppm : | Notes : |
|------------------------------------------------------|-------------|-----------|-------------|-----------|---------|
| 34590-94-8<br>DIPROPYLENE GLYCOL<br>MONOMETHYL ETHER | 308         | 50        | -           | -         | -       |

- UK :

| CAS                                                  | TWA :                 | STEL :                | Ceiling : | Definition : | Criteria : |
|------------------------------------------------------|-----------------------|-----------------------|-----------|--------------|------------|
| 106-97-8<br>BUTANE                                   | 600 ppm<br>1450 mg/m3 | 750 ppm<br>1810 mg/m3 |           |              |            |
| 34590-94-8<br>DIPROPYLENE GLYCOL<br>MONOMETHYL ETHER | 50 ppm<br>308 mg/m3   |                       |           |              |            |

**Derived no effect level (DNEL) or derived minimum effect level (DMEL):**

DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 34590-94-8)

**Final use:**

Exposure method:

Potential health effects:

**Workers.**

Dermal contact.

Long term systemic effects.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

DNEL : 283 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term systemic effects.  
DNEL : 308 mg of substance/m3

**Final use:** **Consumers.**  
Exposure method: Ingestion.  
Potential health effects: Long term systemic effects.  
DNEL : 36 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Long term systemic effects.  
DNEL : 121 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term systemic effects.  
DNEL : 37.2 mg of substance/m3

**HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS**

**Final use:** **Workers.**  
Exposure method: Dermal contact.  
Potential health effects: Long term systemic effects.  
DNEL : 300 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term systemic effects.  
DNEL : 1500 mg of substance/m3

**Final use:** **Consumers.**  
Exposure method: Ingestion.  
Potential health effects: Long term systemic effects.  
DNEL : 300 mg/kg body weight/day

Exposure method: Dermal contact.  
Potential health effects: Long term systemic effects.  
DNEL : 300 mg/kg body weight/day

Exposure method: Inhalation.  
Potential health effects: Long term systemic effects.  
DNEL : 900 mg of substance/m3

**Predicted no effect concentration (PNEC):**

**DIPROPYLENE GLYCOL MONOMETHYL ETHER (CAS: 34590-94-8)**

Environmental compartment: Soil.  
PNEC : 2.74 mg/kg

Environmental compartment: Fresh water.  
PNEC : 19 mg/l

Environmental compartment: Sea water.  
PNEC : 1.9 mg/l

Environmental compartment: Intermittent waste water.  
PNEC : 190 mg/l

Environmental compartment: Fresh water sediment.  
PNEC : 70.2 mg/kg

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

|                                      |                                           |
|--------------------------------------|-------------------------------------------|
| Environmental compartment:<br>PNEC : | Marine sediment.<br>7.02 mg/kg            |
| Environmental compartment:<br>PNEC : | Waste water treatment plant.<br>4168 mg/l |

## 8.2. Exposure controls

### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard ISO 16321.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Let the glove manufacturer advise you on the choice of gloves and their duration of use for your operating conditions

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

Types, classes and filters for respiratory protection above are recommended in case of confrontation at concentrations higher than the exposure limits specified under 8.1. (Control parameters) .They should be adjusted according to actual conditions. they may not be necessary if the product is used outdoors or in a well ventilated area.

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### Physical state

Physical state :  
Fluid liquid.  
Spray.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

**Colour**

Unspecified

**Odour**

Odour threshold : Not stated.

**Melting point**

Melting point/melting range : Not specified.

**Freezing point**

Freezing point / Freezing range : Not stated.

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range : Not specified.

**Flammability**

Flammability (solid, gas) : Not stated.

**Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) Not stated.

:

Explosive properties, upper explosivity limit (%) Not stated.

:

**Flash point**

Flash point interval : Not relevant.

**Auto-ignition temperature**

Self-ignition temperature : Not specified.

**Decomposition temperature**

Decomposition point/decomposition range : Not specified.

**pH**

pH : Not relevant.

pH (aqueous solution) : Not stated.

**Kinematic viscosity**

Viscosity : Not stated.

Viscosity:  $\nu < 7 \text{ mm}^2/\text{s}$  (40°C)

**Solubility**

Water solubility : Insoluble.

Fat solubility : Not stated.

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water : Not stated.

**Vapour pressure**

Vapour pressure (50°C) : Not relevant.

**Density and/or relative density**

Density :  $< 1$

**Relative vapour density**

Vapour density : Not stated.

**Particle characteristics**

The mixture does not contain nanoforms.

**9.2. Other information**

No data available.

**9.2.1. Information with regard to physical hazard classes**

No data available.

**Aerosols**

Chemical combustion heat : Not specified.

Inflammation time : Not specified.

Deflagration density : Not specified.

Inflammation distance : Not specified.

Flame height : Not specified.

Flame duration : Not specified.

**9.2.2. Other safety characteristics**

No data available.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

To be translated (XML)

**10.5. Incompatible materials**

No data available.

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

---

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**11.1.1. Substances**

**a) Acute toxicity :**

No data available.

**b) Skin corrosion/skin irritation :**

No data available.

**c) Serious damage to eyes/eye irritation :**

No data available.

**d) Respiratory or skin sensitisation :**

No data available.

**e) Germ cell mutagenicity :**

No data available.

**f) Carcinogenicity :**

No data available.

**g) Reproductive toxicant :**

No data available.

**h) Specific target organ systemic toxicity - single exposure :**

No data available.

**i) Specific target organ systemic toxicity - repeated exposure :**

No data available.

**j) Aspiration hazard :**

No data available.

**11.1.2. Mixture**

**11.1.2.1 Information on hazard classes**

**a) Acute toxicity :**

Oral route : No data available.

Dermal route : No data available.

Inhalation route (Dusts/mist) : No data available.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

---

**b) Skin corrosion/skin irritation :**

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

**c) Serious damage to eyes/eye irritation :**

Splashes in the eyes may cause irritation and reversible damage

**d) Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

**e) Germ cell mutagenicity :**

Based on available data; the classification criteria are not met.

**f) Carcinogenicity :**

Based on available data; the classification criteria are not met.

**g) Reproductive toxicant :**

Based on available data; the classification criteria are not met.

**h) Specific target organ systemic toxicity - single exposure :**

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

May cause drowsiness or dizziness.

**i) Specific target organ systemic toxicity - repeated exposure :**

Based on available data; the classification criteria are not met.

**j) Aspiration hazard :**

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

Based on available data; the classification criteria are not met.

**11.1.2.2 Other information**

**Symptoms related to the physical, chemical and toxicological characteristics**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

No further relevant information available.

**11.2. Information on other hazards**

**Endocrine disrupting properties**

The mixture does not contain any substance evaluated as an endocrine disruptor with effects on human health.

**Other information**

Repeated exposure may cause skin dryness or cracking

---

**SECTION 12 : ECOLOGICAL INFORMATION**

**12.1. Toxicity**

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Endocrine disrupting properties**

The mixture does not contain any substance evaluated as an endocrine disruptor with environmental effects.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

**12.7. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2025 - IMDG 2024 [42-24] - ICAO/IATA 2025 [66]).

**14.1. UN number or ID number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable

**14.3. Transport hazard class(es)**

- Classification :



2.1

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

| ADR/RID | Class | Code | Pack gr. | Label | Ident. | LQ  | Provis.         | EQ | Cat. | Tunnel |
|---------|-------|------|----------|-------|--------|-----|-----------------|----|------|--------|
|         | 2     | 5F   | -        | 2.1   | -      | 1 L | 190 327 344 625 | E0 | 2    | D      |

| IMDG | Class | 2°Label  | Pack gr. | LQ        | EMS      | Provis.                    | EQ | Stowage Handling | Segregation |
|------|-------|----------|----------|-----------|----------|----------------------------|----|------------------|-------------|
|      | 2     | See SP63 | -        | See SP277 | F-D. S-U | 63 190 277 327 344 381 959 | E0 | - SW1 SW22       | SG69        |

| IATA | Class | 2°Label | Pack gr. | Passager | Passager | Cargo | Cargo  | note           | EQ |
|------|-------|---------|----------|----------|----------|-------|--------|----------------|----|
|      | 2.1   | -       | -        | 203      | 75 kg    | 203   | 150 kg | A145 A167 A802 | E0 |
|      | 2.1   | -       | -        | Y203     | 30 kg G  | -     | -      | A145 A167 A802 | E0 |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Maritime transport in bulk according to IMO instruments**

No data available.

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

---

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Classification and labelling information included in section 2:**

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/1545
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2023/707.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2024/2564. (ATP 22)

**Container information:**

No data available.

**Particular provisions :**

No data available.

**Restrictions applied under Title VIII of Regulation (EC) No. 1907/2006 (REACH):**

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):  
<https://echa.europa.eu/substances-restricted-under-reach>.

**Authorisations agreed under Title VII of Regulation (EC) No.1907/2006 (REACH):**

The mixture does not contain any substance subject to authorisation according to Annex XIV of REACH Regulation (EC) No 1907/2006:  
<https://echa.europa.eu/fr/authorisation-list>.

**Substances that deplete the ozone layer (EC Regulation No. 1005/2009, Montreal Protocol) :**

The mixture does not contain any substance posing a risk to the ozone layer.

**Persistent organic pollutants (POP) (Regulation (EU) 2019/1021):**

The mixture does not contain a persistent organic pollutant.

**PIC Regulation (EU) No 649/2012 concerning the export and import of hazardous chemicals (Rotterdam Convention):**

The mixture is not subject to the Prior Informed Consent (PIC) procedure.

**Explosives precursors :**

The mixture does not contain any substance subject to Regulation (EU) 2019/1148 on the marketing and use of explosives precursors.

**Labelling for detergents (EC Regulation No. 648/2004,907/2006) :**

- 30 % and more : aliphatic hydrocarbons
- allergenic fragrances :  
Citrus Aurantium Peel Oil  
Limonene

**15.2. Chemical safety assessment**

The chemical safety assessment has not been carried out for this mixture.

---

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

|        |                                                       |
|--------|-------------------------------------------------------|
| H220   | Extremely flammable gas.                              |
| H226   | Flammable liquid and vapour.                          |
| H304   | May be fatal if swallowed and enters airways.         |
| H315   | Causes skin irritation.                               |
| H317   | May cause an allergic skin reaction.                  |
| H319   | Causes serious eye irritation.                        |
| H336   | May cause drowsiness or dizziness.                    |
| H400   | Very toxic to aquatic life.                           |
| H412   | Harmful to aquatic life with long lasting effects.    |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |

---

**ANTI GRAFFITI C1 500ML QUICK TECH - A25352**

---

**Abbreviations and acronyms :**

LQ : Limited Quantity

EQ : Excepted Quantity

EmS : Emergency Schedule

E : Packing Instruction

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Moyenne pondérée dans le temps

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

GHS02 : Flame

GHS07 : Exclamation mark

IATA : International Air Transport Association.

IMDG : International Maritime Dangerous Goods.

ICAO : International Civil Aviation Organisation

PBT: Persistent, bioaccumulable and toxic.

PIC: Prior Informed Consent.

POP: Persistent Organic Pollutant.

RID : Regulations concerning the International carriage of Dangerous goods by rail.

SVHC : Substances of very high concern.

AK-ertek : Permissible average concentration